

# OxiQuant S Oxygen Analyser

Used to determine oxygen concentrations in gas mixtures, delivered by oxygen concentrators, blenders...

**ENVITEC**  
by Honeywell



- Flexible manual calibration
- Auto-off (after 3 minutes)
- Response time: <13 seconds to 90% of value
- Sensor (with integrated battery) can be replaced

The OxiQuant S oxygen analyser is used to determine oxygen concentrations in gas mixtures. It can be used to monitor gas supply equipment in industry and hospitals or to check breathing mixtures in diving systems (Nitrox and Trimix mixtures).

Its compact dimensions, low weight, easy handling and calibration make the device particularly suitable for mobile applications.



The OxiQuant S is neither designed for personal protection nor for monitoring medical breathing air in direct contact with patients. It must not be used for the preparation of gas mixtures, but to monitor them.



# OxiQuant S Oxygen Analyser

<b>Measuring Range</b> Oxygen	0 - 100% O <sub>2</sub>
<b>Display</b> Resolution	0.1% oxygen
<b>Precision</b>	< 1% volume O <sub>2</sub> , when calibrated at 100% vol.O <sub>2</sub>
<b>Offset</b>	< 1% volume O <sub>2</sub> in 100% N <sub>2</sub>
<b>Response time</b>	< 13 seconds to 90% of final value
<b>Linearity error</b>	< 3% relative
<b>Drift</b>	< 1% volume O <sub>2</sub> over 8 hours
<b>Cross-sensitivity</b>	< 1% volume O <sub>2</sub> in reaction to: 10% CO <sub>2</sub> , rest N <sub>2</sub> 80% N <sub>2</sub> O, rest N <sub>2</sub> 7.5% halothane, rest N <sub>2</sub> 7.5% isoflurane, rest N <sub>2</sub> 7.5% enflurane, rest N <sub>2</sub> 9% sevoflurane, rest N <sub>2</sub> 20% desflurane, rest N <sub>2</sub>
<b>Effect of humidity</b>	< 1% O <sub>2</sub> between 0 and 100% RH at 25°C
<b>Effect of pressure</b>	Proportional to the change in oxygen partial pressure
<b>Operational pressure range</b>	750 - 1250 hPa
<b>Sensitivity to impact</b>	< 1% relative after falling from a height of 1m
<b>Temperature</b> Operating temperature Temperature compensation Operating humidity Storage temperature Recommended storage	0°C – 50°C Integrated NTC compensation 0 – 99% RH -20°C – 50°C 5°C – 15°C
<b>Sensor life</b>	>500,000 % oxygen hours
<b>Battery service life</b>	approximately 1100 operating hours (battery integrated in sensor)
<b>Weight</b> <b>Dimensions</b>	Approximately 90g 92 mm (L) x 57 mm (D)
<b>Warranty</b>	Analyser 24 months, sensor 15 months

**Part Numbers**  
Envitec OxiQuant S Oxygen Analyser 0111275  
Standard accessories included:



**3 digit display**

### Over range

At oxygen concentrations above 99.9% the concentration is displayed without a decimal place number or decimal point.

For example:

1 0 0 corresponds to 100% O<sub>2</sub>

1 0 1 corresponds to 101% O<sub>2</sub>

\* in accordance with ISO 9919:2005 Standards.

Specifications Subject to Change



Distributed by:

# ENVITEC

by Honeywell

**EnviteC-Wismar GmbH**  
a Honeywell Company  
Alter Holzhafen 18, 23966 Wismar, Germany  
Phone: +49 (0) 3841 / 360-1  
Phone: +49 (0) 3841 / 360-200 Sales  
Fax: +49 (0) 3841 / 360-222

**Internet:**  
www.envitec.com

**E-mail:**  
info@envitec.com



Part Number: 0191205  
Date: 08/15



ISO 13485:2003